

vion seating | product specification

Mesh Back Guest Seating Models 6324, 6325, 6334 & 6335

Dimensions

Without Arms (Models 6324 & 6334)

Overall Depth		24 in / 610 mm
Overall Width		20 in / 508 mm
Overall Height		34.5 in / 876 mm
Seat Depth		18 in / 457 mm
Seat Width		19 in / 483 mm
Seat Height		17.5 in / 445 mm
Back Height - From Seat		17 in / 432 mm
Product Weight	6324	17 lbs / 7.7 kgs
	6334	18 lbs / 8.2 kgs
Shipping Cube		11.75 ft ³ / 0.33 m ³

With Arms (Models 6325 & 6335)

Overall Length		24 in / 610 mm
Overall Width		25.5 in / 648 mm
Overall Height		34.5 in / 876 mm
Seat Depth		18 in / 457 mm
Seat Width		19 in / 483 mm
Seat Height		17.5 in / 445 mm
Back Height - From Seat		17 in / 432 mm
Armrest Clearance		20 in / 508 mm
Arm Height - From Seat		8.5 in / 216 mm
Product Weight	6325	19 lbs / 8.6 kgs
	6335	20 lbs / 9.1 kgs
Shipping Cube		13.5 ft ³ / 0.39 m ³

Contact sales rep for more information.

Features

- Elasticized, breathable mesh back
- Wall saver leg design prevents chair back from damaging walls

Options

- 10 standard mesh colours are available
- Back frame is available in black or fog colour
- Chair legs are coloured black, fog, tungsten, or charcoal, as standard. Also available in chrome finish
- Matching upholstery program available to provide a uniform 360° look
- Seat foam can be upgraded to memory foam
- Dual-wheel, hard flooring caster models are optionally available

MODELS 6324C, 6325C, 6334C, & 6335C

- Carpet casters are standard. Hard surface casters are available

Construction (Frame)

- Metal tubing, 0.875 in (22 mm) diameter
- Polypropylene shroud on underside of seat frame prevents imprints or damage to upholstered chairs when stacked

Construction (Arms)

MODELS 6325 & 6335

- Durable nylon arms
- Waterfall front edge

Construction (Seat)

- Laminated hardwood veneer seat, 0.5 in (13 mm) thick, 9-ply



6325-CHM (with chrome frame)



6334



6335C (casters)



vion seating | product specification

Construction (Back)

- Polypropylene back frame
- Steel connections to chair frame

Construction (Glides)

- Standard polypropylene glides
- Opaque white non-marking glides available on request
- Optional self-leveling glides, cushioned steel

Upholstery (Seat)

- Seat is upholstered in fabric, vinyl, or leather
- Front edge of seat is a seamless waterfall

Upholstery (Back)

MODELS 6324 & 6325

- Elastomeric mesh back

MODELS 6334 & 6335

- Can be upholstered in fabric, vinyl, or leather
- Rear side of back is upholstered in black fabric, or optionally, a fabric matching seat and/or back

Foam

- Seat foam is 2.5 in (64 mm) thick layer

MODELS 6334 & 6335

- Back foam is 0.25 in (6 mm) thick
- Density: 1.5 lbs, ILD: 40

Weight Capacity

Designed for a static load of 1000 lbs and an active weight capacity of 300 lbs per seat.

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foams and fabrics
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All fabric and foam is tested and certified, meeting CAL 117 standards. Chair may meet CAL 133 requirements with certain upholstery selections.

Environmental

View [Environmental Data Sheets](#) online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities
- Greenguard Gold Certified (Indoor Air Quality)
- level® e3 Sustainability Certified: Level 3

